

Features

Smart Eye-Care Solution

RP860K provides proprietary eye-care technology with Flicker-Free performance and Low Blue Light emission preventing eyestrain and fatigue. With embedded motion sensors, the Smart Eye-Care solution can function intuitively. Advanced anti-glare screen treatment minimizes reflections and glare.

Germ-Resistant Screen

The Germ-Resistant Screen with a multilayer coating of non-toxic, long-lasting ionic silver nano agent can kill most bacteria on contact while effectively blocking the spread of germs in classrooms.

EZWrite 4.0 Annotation Tool

Microsoft Office documents can be instantly opened with EZWrite 4.0 for easy and fun annotations. The Floating Toolbar allows quick access to frequently used tools such as Whiteboard, Annotation Tools and Video Recording. Text, numbers, forms, and drawings are instantly converted with Intelligent Handwriting Recognition. Erasing is done with a palm swipe. And Tool Box includes features such as Calculator, Geometry Recognition, Timer, Buzzer, Team Post and Score Board.

Intuitive Design

The smart teaching design of RP860K incorporates front I/O, a sound bar with two front speakers and integrated pen tray. It is equipped with NFC sensor and NFC pen.

InstaQShare Wireless Collaboration Solution

Integrated InstaQShare app enables easy wireless presentation and collaboration by screen mirroring. Launching the host app and downloading the client app onto an Android, iOS, Mac or Windows device, up to 16 participants can instantly stream content like presentations and full HD videos smoothly.

Smart Account Management System

Smart AMS features multi-account management via NFC technology allowing teachers to directly access personal system settings simply by tapping an ID card on the RP860K's front-bezel sensor.

Input and Output Terminals





* Touch 1 works only with HDMI 1 and HDMI 2.

* Touch 2 works only with HDMI 3, DisplayPort Input and VGA Input.

RP860K 86'' Interactive Flat Panel Education



Specifications			
	Screen Size		86"
	Resolution		3840 × 2160
Panel	Brightness (Typ.)		330 nits
	Contrast Ratio (Typ.)		1200 : 1
	Viewing Angle (H / V)		178° / 178°
	Response Time (G-t-G)		8ms
	Backlight Life		30,000 hours
	Operating Hours		18 / 7
	Orientation		Landscape
Power	Туре		Internal
	Power Supply		100V ~ 240V, 50Hz / 60Hz
		Maximum	530W
	Power Consumption	Typical	371W
		Standby mode	<0,5W
		Off Mode	0W
	AC Power Switch	On Hode	Yes
	Wake up		VGA / HDMI
	Technology, Number of Touches		IR, 20 points
Touch	Interface		USB x 2
	Tempered Glass, Hardness		4 mm, 7H
Glass	AG Coating		80%
Caring	Eye-Care Solution		Smart Eye-Care
	Germ-Resistant Screen		Yes
	Operation Temperature		0°C ~ 40°C
Environment	Operating Humidity		10% ~ 90% RH non-condensing
Connectivity		VGA	x
	Input	HDMI 2.0	x I
		HDMI I.4	×2
		Display Port	xl
		Audio Input	× I (3.5 mm)
	Output USB	HDMI	x l
		Audio Output	× I (3.5 mm)
		USB 3.0	×I
		USB 2.0	× 5
	RS232		Yes
	RJ45		Yes
	Remote Controller		Yes
Audio	Internal Speaker		16W × 2
		Screen	1988 x 1230 x 129 mm
	Dimension	Package	2211 × 1420 × 280 mm
	Weight	Screen	81 kg
Mechanical		Package	108 kg
	Bezel Width		34 mm (Top / Side), 104 mm (Bottom)
	Wall Mounting (VESA)		800 × 400 mm
	(Screw Type / Max. Length)		M8 x 25 mm
	(Serew type / Flax. Length)		
	Slot-in PC		Yes
			Yes Yes
	Slot-in PC		
	Slot-in PC Compartment for Wi-Fi dongle		Yes

Dimensions





BenQ Europe B.V.

Meerenakkerweg I-17 5652 AR Eindhoven The Netherlands Tel: +31 88 8889200 © 2017 BenQ Corp. Specifications may vary by region, please visit your local stores for details. Actual product's features and specifications are subject to change without notice. This material may include corporate names and trademarks of third parties which are the properties of the third parties respectively.



Scan the QR Code for more information



BenQ.eu