

Destboard     V	ing Stift Tousk	IAN <sup>2</sup> Terrals	Analyse Touck			
PLSIP Extensis	on SIP Trunk	IAX2 Trunk	Analog Trunk 2/2			
Extensions Y CPU	<ul> <li>Current calls</li> </ul>	<ul> <li>Memory</li> </ul>	n			
Inbound Control V 100 %	100					
Outbound Control v 80 %	10		FN -			
Audio Library 🗸 🗸 🕫 %	60					
Advanced Features v 40%				Used		
Preferences ~						
20 % Feature Codes			Cached			
Le Reports v 1501:25 1501:40	1501.55 1502.10 1502.25 1502.40 1502.55 1501.40	15 01 55 15 02:10 15 02:25 15 02:40 15 02:55				
d <sup>2</sup> Addons Y Call Statistics	Storage	System	n Info			
System ~ 14	6.08	Model		Cosl/ax-T100/T100S		
12	5.08	Device		IP Phone System		
10	4.08	WAN 5		192.168.17.147 68:69:11:22:33:44		
	3.08	LIN P		192.168.10.100		
- +	2.68	LAN M		68:69:25:22:33:44		
4	1 68	Hardwo	ine Version	v4		
2 00:00 00:00 06	12:00 12:00 13:00 18:00 21:00 08	System				
Configuration Wizard						
				• •	•	
		PV	VR SYS WAN	LAN 1	2	
		CooVox T100				



# **IP Phone System**

CooVox T100 is an easy-to-config and delicate diminutive IPPBX system specially designed for small and medium-sized enterprises worldwide. CooVox T100 is well suited for small businesses with up to 100 people and meets all the needs of an office phone system. When used with the G Series VoIP Gateway, T100 supports mixed networking of analog phones and VoIP phones. External lines can be selected from analog lines or VoIP lines. Equipped with the brand-new software 4.0 system, CooVox T100 can provide users with more convenience in application and management. Plus, it can improve enterprise communication efficiency, and help enhance enterprise value.

### **Application Scenarios**



Financial

Institution



Venue







Warehouse



National Park

## Feature Highlights



#### **Endpoints Provisioning**

Quick and straightforward deployment of endpoint devices using the Plug-and-Play auto-provisioning feature. Users can scan the QR code to complete the registration on the CooCall softphone.



#### **Proxy Services**

No fixed public IP, third-party DDNS services, and VPN router are required. Remote extension and remote branch office phone system integration have never been easier!



#### **CooCall Softphone**

CooCall softphone brings users a new office phone system experience while using the CooVox IPPBX v4. CooCall is like a desk phone that can take your office anywhere. Users can answer calls, dial calls, and even dial international calls through the office's IPPBX.



#### **3rd Party Compatible**

In addition to the built-in phone system functions, CooVox T100 is also compatible with third-party SIP systems, including standard SIP endpoints, CRM systems, and collaboration tools to expand the existing IP voice communication function.

<b>O</b>

#### **G** Series Gateway Provisioning

Support use with G Series Gateways, which can help users quickly deploy analog phones, or backup, and restore the gateway's configuration on it.



**Operator Panel** 

The Operator Panel is a comprehensive software specially designed for the CooVox series of IPPBX. By using the Operator Panel, users can achieve features such as live paging, emergency paging, high-quality background music, scheduled paging, scheduled music, etc.



The control center can manage each authorized PBX in a unified manner through the remote management system, realizing remote switching off equipment, viewing real-time data, and collaborative user troubleshooting.



#### Billing

With a built-in billing system, no third-party billing software is required.Prepaid/postpaid billing, billing credit, flexible billing rates, and billing statistics features are all supported.

## Hardware Specifications

Specifications	
Dimension	170mm*115mm*30mm
Weight	0.6kg
Analog Interface	2 Port (Interface standard RJ11; FXO outside line or FXS inside line)
CPU	ARM 4 Core
RAM	1GB DDR3
Storage (SD Card)	8G SD Card (Industrial grade)
USB (Extended Storage Supported)	1 Port(File system format: FAT16, FAT32, EXTFAT, NTFS, EXT3, EXT
Ethernet Interface	WAN, LAN (10/100Mbps)
Console Port	1 Port(Rate 115200)
Reset Key	Support
Power	DC 12V-1A

# Software Specifications

System Capacity	<ul> <li>☑ 100 Extensions</li> <li>☑ 50 Simultaneous Calls</li> <li>☑ 30 Conference Attendees (Recommended)</li> <li>☑ 50 Conference Attendees (Maximum)</li> <li>☑ 400 hrs Recording (Internal Storage)</li> </ul>	☑ Unlimited IVF ☑ Unlimited Nu ☑ Unlimited Ph	R Levels mber of Queues onebook Contacts Paging Members ded)	1TB USB Expansion Storage Unlimited Number of Incoming Routes Unlimited Number of Outbound Routes	
Protocols & Codecs	<ul> <li>SIP(RFC3261), IAX2</li> <li>DTMF(RFC4733, SIPINFO, In-Band)</li> <li>Transport Protocols:UDP,TCP,TLS,SRTP</li> <li>Network Protocols:IPv4, IPv6, VLAN, DHCP, PPPoE, DDNS, NTP, SNTP, TFTP, SSH, HTTPS, LDAP</li> <li>Video Codecs:VP8,H.264,H.263+,H.263,H.261</li> <li>Audio Codecs:Opus, G.722, G.711(a-law,u-law), G.729, G.726, GSM, SPEEX,AMR,AMR-WB</li> </ul>				
Telephony Features	Image: Ring Group       Image: Call Forward         Image: Call Forward       Image: Call Forward         Image: Call Waiting       Image: Call Forward         Image: Call Forward       Image: Call Forward         Image: Call Waiting       Image: Call Forward         Image: Call Forward       Image: Call Forward         Image: Call Waiting       Image: Call Forward         Image: Call Forward       Image: Call Forward	Caller ID Call Spy Video Call 3-way Calling Conference Call Follow Me Call Back DISA Smart DID	<ul> <li>Blacklist</li> <li>Voicemail</li> <li>Wakeup Call</li> <li>PIN Code</li> <li>Do Not Disturb</li> <li>Switch Call</li> <li>Time Conditions</li> <li>Paging &amp; Interconditions</li> </ul>	<ul> <li>One Number Stations</li> <li>Music On Ringback</li> <li>Distinctive Ringtone</li> <li>Auto Call Recording</li> <li>One Touch Recording</li> <li>Web Extensions (WebRTC)</li> </ul>	
Feature Highlights	<ul> <li>Remote Management</li> <li>Softphone APP Auto Provisioning (QR Code Scan)</li> <li>IP Phone Auto Provisioning (PNP &amp; Quick Register Code)</li> <li>LDAP Phonebook Auto Configure (H81, H83)</li> <li>EX16S Auto Provisioning</li> <li>SIP Proxy (NAT Traversal)</li> <li>Open API Interface for Secondary Development to Connect with 3rd Systems</li> <li>Multilingual Interface: Simplified Chinese, Traditional Chinese, English, Russian</li> <li>Multilingual System Voice: Chinese, English, Spanish, French and other 24 languages</li> </ul>				

#### ZYCOO Communications LLC

Multi-level User Administration	<ul> <li>Admin user: All Privileges</li> <li>Operator user: Extensions, faxes, CDR, recordings, etc.</li> <li>Extension user: WebRTC, recordings, voicemails, call logs, etc.</li> <li>Billing user</li> <li>Operator panel user</li> </ul>
Security	<ul> <li>Firewall based on iptables</li> <li>Geo-IP (Security policy based on IP address geographical locations)</li> <li>Intrusion auto detection and prevention</li> <li>IP Black/White List</li> <li>Extension Permit IP</li> <li>Data Backup and Recovery</li> </ul>
Network Features	<ul> <li>Network (WAN): Static IP, DHCP, PPPoE</li> <li>VPN: PPTP, OpenVPN,</li> <li>Static Routing</li> <li>DHCP Server</li> <li>VLAN (WAN&amp;LAN Interface)</li> <li>Virtual IP</li> <li>SIP Proxy (NAT Traversal)</li> </ul>

 $\rangle$ 



zycoo@zycoo.com www.zycoo.com © 2024 Zycoo Communications LLC All rights reserved